

<b>Hull LOA:</b>	Max. Monohull	16m (53')* 18m (60')**
	Max. Multihull	11m (36')* 13m (43')**

<b>Sail Area:</b>	Max. Monohull	53m <sup>2</sup> (570ft <sup>2</sup> )* 60m <sup>2</sup> (646ft <sup>2</sup> )**
	Max. Multihull	42m <sup>2</sup> (452ft <sup>2</sup> )* 48m <sup>2</sup> (517ft <sup>2</sup> )**

\*Maximum limits using shortest Headboard car and Batten cars.

\*\*Maximum limits using longest Headboard car and Batten cars.

**Mast details** (If known):


Spar Manufacturer	
Mast Type	
Profile No.	

**Mainsail details:**

Luff Length (P)	
Foot Length (E)	
Qty. Full Length Battens	

**Ballslide Series 8**

See [www.ronstan.com](http://www.ronstan.com) website for car and feet selection table



Feet required for cars;

**RC284xx**

For luff groove openings greater than 12mm (1/2").


Feet not supplied with cars.

Feet sold in pairs.

Fasteners included.

See website [www.ronstan.com](http://www.ronstan.com) for mast compatibility tables.

RC20130	Qty	Pairs
RC20131	Qty	Pairs
RC20132	Qty	Pairs
RC20133	Qty	Pairs



Feet supplied with cars;

**RC281xx**

For luff groove openings of approximately 4.5mm (3/16").

See website [www.ronstan.com](http://www.ronstan.com) for mast compatibility tables.

